

KTP
EVO **4**

REF.
KTPEVO4



FULL BODY HARNESS + 2 M ELASTIC WEBBING LANYARD WITH INTEGRATED SHOCK ABSORBER



UNIQUE CONCEPT



The bag

The harness

The lanyard





TECHNICAL SPECIFICATIONS

- **Harness in unique size**
- 1 • Water repellent webbing in polyester 44 mm ($R \geq 25kN$)
- 2 • Reversible bag made of fluo neoprene fitted with a comfort back pad
- 3 • Shoulder straps adjustment pulling downwards with steel black powder coated quick buckles male/female
- 4 • Chest strap 44 mm and legs straps fastening through black zinc plated automatic buckles with locking indicator
- 5 • Back fall arrest D ring in metal
- 6 • Patented anti-trauma buckles in zinc plated steel
- 7 • Removable lanyard-holder
- 8 • Large back plate in polypropylene
- Static resistance ≥ 15 kN
- 9 • Lanyard with a tubular sheath 1,2m (2m extended), wide 50 mm
- Integrated tearing web limiting the braking force to 450 daN
- 10 • Aluminum connector with large opening 60 mm
- Total weight : 2,25 kg

DESCRIPTION

The KTP harnesses proposed by NEOFEU are unique on the market: the bag, the harness and the lanyard cannot be dismantled. They provide a complete personal protective system against fall, usable instantly.

The KTP EVO 4 is made up of a full body harness and of an elastic lanyard with integrated shock absorber.



USE



Industrial maintenance



Antenna, air-conditioning



Metal construction



Joiner, blind provider



Chimney sweep



Bridge maintenance

MINIMUM CLEARANCE AND FALL FACTORS

REFERENCE	FALL ARRESTER LENGTH (extended)	Max user weight	MINIMUM CLEARANCE		
			F0	F1	F2
KTPEVO4	2 m	100 kg	$\geq 2,75$ m	$\geq 4,75$ m	$\geq 5,90$ m

