

FULL BODY HARNESS

neofeu)

neofeu.com

REF.
NUS55FALL PROTECTION ONLY*
*Un seul métier, l'antichute

CERTIFICATION : EN 361 : 2002 / REGULATION : 2016 / 425

TESTED
140 KGLarge back fall arrest
D ring in aluminumFront fall arrest
webbing loopShoulder straps adjustment
pulling downwards

Drop indicators

Quick buckles for
leg strap adjustment

TECHNICAL SPECIFICATIONS

- Tested to 140 kg
- Webbing in polyester 44 mm ($R \geq 25$ kN)
- Shoulder straps adjustment pulling downwards with black zinc plated quick buckles male/female
- Chest strap 44 mm and legs straps adjustment through black zinc plated quick buckles
- Drop indicators showing at 300 daN
- Static resistance ≥ 15 kN
- Weight : 1 kg

Other version :

- With integrated work positioning belt Ref. NUS55C

USE

Full body harness to use in case of fall hazard. Intended to maintenance works in industry and the construction area.

DESCRIPTION

Fullbody harness bicolor in polyester webbing with 2 fall arrest attachment points : 1 front loop and 1 back large aluminum D ring. Easy to adjust with slide buckles on shoulder straps, pulling downwards and quick buckles on legs. It is fitted with 2 fall indicators.

TAILLE / SIZE	80 cm \leq Size S \leq 105 cm 90 cm \leq Size M-L \leq 115 cm 100 cm \leq Size XL \leq 135 cm
	65 cm \leq Size S \leq 105 cm 85 cm \leq Size M-L \leq 120 cm 105 cm \leq Size XL \leq 130 cm
	45 cm \leq Size S \leq 65 cm 50 cm \leq Size M-L \leq 75 cm 60 cm \leq Size XL \leq 80 cm
	155 cm \leq Size S \leq 175 cm 165 cm \leq Size M-L \leq 188 cm 170 cm \leq Size XL \leq 200 cm